

IN THE CLAIMS

Claim 1 (currently amended): A product packaging and displaying device ~~mainly comprises~~ comprising:

a holding body and a covering body;

said holding body ~~with its~~ including one side having a protruded hanging part for hanging purpose, another side having a plurality of protruded positioning parts for one end of a display product to ~~sleeve on~~ engage thereon, and a connecting part for a sleeving and covering ~~body part~~ to connect onto, said positioning parts ~~are~~ being evenly disposed ~~between two said connecting parts on said~~ holding body, each said positioning part ~~is~~ being formed by two parallel pieces, each said parallel piece having a locking device disposed on ~~the~~ outer side for pressing against the display product, ~~each~~ said connecting part having more than one positioning hole, a display part ~~is~~ being protruded and disposed between said positioning part and said hanging part, a width of said display part ~~is~~ being slightly wider than the outer edges of said display product;

said covering ~~part is~~ body being connected and disposed on one side of said holding body, in which said display product is ~~sleeved~~ disposed on the same side, said covering ~~part~~ body having said sleeving and covering ~~body part~~ in corresponding to said positioning part, a hollow connecting board ~~is~~ being disposed at each end of said

covering body, said connecting board having a locking piece to lock with said positioning hole of said connecting part, for fixing said connecting part of said holding body, the outer diameter of said sleeving and covering part ~~is~~ slightly being wider than the width of the outer edges of said display product;

~~accordingly, the present invention provides a convenient and stable structure of assembly of said holding body and covering body, when said display product is placed between said holding body and said covering body, its maximum width is small than that of said display part and said sleeving and covering part, so that said display product will not be damaged if falls off.~~

Claim 2 (currently amended): ~~A~~ The product packaging and displaying device as claimed in Claim 1, wherein said display part is hollow, with its two ends protruded outward.

Claim 3 (currently amended): ~~A~~ The product packaging and displaying device as claimed in Claim 1, wherein said sleeving and covering part of said covering ~~part can be~~ body is formed as the same structure of said positioning part of said holding ~~part, or as protruded structure~~ body for ~~sleeving~~ attaching products with holes, for placing and positioning ~~of~~ said display product ~~of a socket with both ends having a hole.~~

Claim 4 (currently amended): ~~A~~ The product packaging and displaying device as claimed in Claim 1, wherein said positioning part of the holding ~~part can be~~ body is formed as a hollow sleeve-ring structure in corresponding to said sleeving and covering part, for ~~sleeving~~ attaching said display product ~~of~~ having both ends in protruded rod structure.

Claim 5 (currently amended): A product packaging and displaying device ~~mainly comprises~~ comprising:

a holding body and a covering body;

one side of said holding body having a hollow display part protruded outward, another side having a protruded positioning part for one end of ~~said~~ a display product to ~~sleeve on~~ attach thereon, and a connecting part for connecting to a sleeving and covering part, a width of said display part ~~is slightly being~~ is wider than ~~the~~ a maximum width of said display product;

said covering part ~~is~~ being connected and disposed on one side of said holding body, in which said display product is ~~sleeved~~ disposed on the same side, said covering ~~part~~ body having said sleeving and covering ~~body~~ part in corresponding to said positioning part, a hollow connecting board ~~is~~ being disposed at each end of said covering body, the outer diameter of said sleeving and covering part ~~is slightly being~~ is wider than the width of the

outer edges of said display product;

~~accordingly, the present invention provides a convenient and stable structure of assembly of said holding body and covering body, when said display product is placed between said holding body and said covering body, its maximum width is small than that of said display part and said sleeving and covering part, so that said display product will not be damaged if falls off.~~

Claim 6 (currently amended): ~~A~~ The product packaging and displaying device as claimed in Claim 5, wherein said positioning parts are evenly disposed ~~between two said connecting parts~~ on said holding body, each said positioning part is formed by two parallel pieces, ~~the~~ a width of two said parallel pieces equals to ~~the~~ a hole diameter of said display product, each said parallel piece ~~having~~ includes a locking device disposed on ~~the~~ an outer side for pressing against the display product.

Claim 7 (currently amended): ~~A~~ The product packaging and displaying device as claimed in Claim 5, wherein said connecting part is disposed at each end of said holding body, more than one positioning hole are ~~disposed on~~ formed in said connecting part, a locking piece is protruded and disposed on said connecting board of said covering body, ~~accordingly,~~ said locking piece locks with said positioning hole, for fixing said connecting part to

said connecting board.

Claim 8 (currently amended): ~~A~~ The product packaging and displaying device as claimed in Claim 5, wherein said sleeving and covering part is a ring-shaped structure for ~~sleeving~~ attaching on said display product.

Claim 9 (currently amended): ~~A~~ The product packaging and displaying device as claimed in Claim 5, wherein said sleeving and covering part of said covering ~~part can be~~ body is formed as the same structure of said positioning part of said holding ~~part, or as protruded structure~~ body for ~~sleeving~~ attaching products with holes, for placing and positioning ~~of~~ said display product ~~of a socket with both ends having a hole.~~

Claim 10 (currently amended): ~~A~~ The product packaging and displaying device as claimed in Claim 5, wherein said positioning part of the holding ~~part can be~~ body is formed as a hollow sleeve-ring structure in corresponding to said sleeving and covering part, for ~~sleeving~~ attaching said display product ~~of~~ having both ends in protruded rod structure.